

Enjoy More Power, Less Weight

Marson is making installation more efficient with the BT-2A battery-powered rivet tool. It features all the reliability and performance you would expect from Marson, along with superior features and specifications:

- Samsung® Extended-Life Battery
- Faster Charging Cycle
- Advanced Trigger Mechanism
- Redesigned, Ergonomic Grip
- Lighter Weight & Superior Balance
- Left or Right-Handed Belt Clip
- LED Light to Illuminate Rivet Application

Capacity: 3/32" (2.4 mm) – 3/16" (4.8 mm)

Stroke Length: 0.83" (21mm)

Pulling Force: 2,248lbs (10,000 N)

Weight (with Li-ion battery pack): 4lbs (1.8kg)

Battery Pack: 16V / Li-ion / 2AH

Recharge Time: Approximately 30 minutes

Tool Accepted: Li-ion

The Marson BT-2A includes nose tips for 3/32", 1/8", 5/32" and 3/16" rivet sizes* and is ideal for applications ranging from construction, furniture assembly, lighting fixtures, signs, trailers and many more.

*Optional nose tips for 3/16" Monobolts are also available



Li-ion battery charger

PART No.	DESCRIPTION	NOTES
M39480	BT-2A TOOL KIT (INCLUDES ONE TOOL WITH BATTERY, BATTERY CHARGER, AND CARRYING CASE)	RECEIVE 3 ADDITIONAL BATTERIES FREE, WITH A PURCHASE OF 3 KITS
M39483	BT-2A EXTRA BATTERY (2AH - 16V)	EACH KIT (M39480) COMES WITH ONE BATTERY
M39484	BT-2A HIGH-CAPACITY BATTERY (4AH - 16V)	OPTIONAL HIGHER CAPACITY BATTERY IS NOT INCLUDED IN KIT
M38985	BT-2A BATTERY CHARGER	EACH KIT (M39480) COMES WITH ONE BATTERY CHARGER

afs-idg.com/marson

Disclaimer:

The information contained in this publication is only for general guidance, and is not intended to create any warranty, express, implied, or statutory; all warranties are contained only in Howmet Fastening System's written quotations, acknowledgments, and/or purchase orders. It is recommended that the user secure specific, up-to-date data and information regarding each application and/or use of such products.

©2020 Howmet Aerospace Inc. All rights reserved.

HFS Industrial Distribution

1925 North MacArthur Drive
Tracy, CA 95376
Tel: 800 826 2884
Fax: 800 573 2645